

# WLg-LINK

Compact access point, Ethernet bridge & repeater (WDS)



- IEEE 802.11 a/b/g & super AG standards, up to 108 Mbps data rate
- Security: WEP, WPA-PSK, WPA2-PSK and IEEE 802.1x (RADIUS)
- Easy to use web based configuration
- Auto-sensing 10/100 Base TX RJ45 network interface
- +9VDC to +48VDC power supply
- Small sized enclosure (L: 103 x W: 67 x H: 24 mm)



## Introduction

When used in access point mode, WLg-LINK is the root element of an industrial WiFi Ethernet network. When used as a bridge, it makes it possible to connect any Ethernet 10/100 industrial equipment to this network.

WLg-LINK device is also designed to work as a wireless bridge between the wired MODBUS/TCP protocol and the radio network, this feature allows connecting any MODBUS/TCP equipment to this network.

Integrators and manufacturers (point of sales, medical instrumentation, industrial automation, security systems, video surveillance, automotive, building automation ...) can right now rely on this new technology to build safety wireless network applications while freeing themselves from wiring constraints.

## Technical characteristics overview

<b>Ethernet link</b>	10/100 Base TX Ethernet interface, RJ45 connector
<b>WiFi network</b>	Compliant to the IEEE 802.11a/b/g 2.4 / 5 GHz standards, multi-country Roaming support (IEEE 802.11d); Dynamic Frequency Selection (DFS) support provides flexible selection of best frequency to allow mobility among all existing IEEE 802.11a/b/g networks; «ClearVoice» band provides non-overlapping channels for fast-speed data transmission; Transmission Power Control (TPC) offers flexibility to adjust RF output power, based on the Atheros's AR5414 (AR5006XS) chip set.
<b>Data rate</b>	Up to 108 Mbps (Super AG mode)
<b>Channels</b>	13 channels (b/g modes), 8 channels (a mode), 11 channels (h mode)
<b>Output power</b>	Transmitter +20 dBm (TPC)
<b>Sensitivity</b>	Receiver -92 dBm for IEEE 802.11 a/g and -95 dBm for IEEE 802.11b
<b>Antennas</b>	Two 2dBi 2.4 / 5 GHz antennas (RP-SMA connectors)
<b>Modulation</b>	OFDM: BPSK, QPSK, 16QAM, 64QAM DSSS: DBPSK, DQPSK, CCK
<b>Security</b>	64/128 bits WEP, WPA-PSK, WPA2-PSK, IEEE 802.1x (RADIUS authenticator & supplicant), MAC addresses filtering, SSID broadcast control
<b>Modes</b>	Access point to build a WiFi network infrastructure, Bridge to connect any Ethernet equipments to this network and MODBUS/TCP wireless gateway, repeater (WDS), infrastructure, AD-HOC, bridge router & fast roaming (less than 50 ms) modes are supported
<b>Administration</b>	Thanks to its built-in WEB interface, the setup of the device is achieved using any web browser installed on your computer (Internet Explorer, Netscape, Mozilla ...), SNMP agent, ACKSYS NDM
<b>Operating systems</b>	Windows, Linux, UNIX as well as any operating system supporting TCP/IP
<b>Signaling</b>	LAN & WLAN activity on LEDs
<b>Power supply</b>	+9VDC to +48VDC power source, 3-pin Phoenix terminal block
<b>Consumption</b>	3.5 Watts typical, 5 Watts maximum
<b>Dimensions &amp; weight</b>	Small sized enclosure L: 103 x W: 67 x H: 24 mm, weight 225 g
<b>Environment</b>	Operating temperature: 0°C to +70°C, storage: -65 to +100°C Humidity: 5% to 95% (non-condensing)

## Ordering references

WLg-LINK	Access Point, Ethernet Bridge, repeater (WDS) module for wireless WiFi IEEE 802.11a/b/g & super AG, shipped with two 2dBi 2.4 / 5 GHz antennas
PWS12-UNI-PH3	AC (110V / 220V) to 12VDC power adapter with cable terminated by a 3-pin Phoenix terminal block

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.