

AirWan-M12

11n WiFi and 4G cellular router with positioning (GNSS), for road applications and tramway



- 4G LTE router + positioning (GNSS)
- WiFi router (with fast roaming <30ms) or access point
- M12 & FAKRA connectors, ITxPT compliant
- Automatic Cellular <> WiFi switching
- Designed for road & trams applications
- ECE R10, EN50155, shocks & vibrations proof...
- Compact case, wall mounting
- Centralized administration and configurations management



Introduction

AirWan-M12 is a simple, reliable and cost-effective solution for connecting fleets of vehicles such as buses, trams, trucks, emergency and public safety vehicles, etc., thanks to its cellular (2G/3G/4G LTE), dual-band WiFi (2.4/5GHz) and GNSS (GPS, Galileo, GLONASS, Beidou) interfaces, as well as its 2 Fast Ethernet ports.

Mobility : AirWan-M12 is equipped with high-speed wireless technologies for transmitting data to and from vehicles. For public transport applications (bus and trams), AirWan-M12 makes it possible to pool all data streams (SAE, ticketing, PIS, CCTV...) on a single router. Its WiFi roaming capabilities (<30 ms) ensure continuous data transmission as buses move at the depot. Its automatic switching capabilities between WiFi and 4G/LTE ensure service continuity when they go into operation. AirWan-M12 allows vehicles tracking with its GNSS feature. It is also rugged (shock and vibration proof), E-marked ECE R10 and maintenance-free.

Administration and product monitoring : can be achieved directly from a web browser or from WaveManager, the centralized administration software provided by ACKSYS. Besides, its advanced routing and filtering functions make it easy to deploy large fleets of vehicles.

Technical Characteristics overview

| | |
|---|--|
| Ethernet Interface | 2 ports Fast Ethernet 10/100 auto-sensing, Base TX, auto MDI/MDIX, 4-points M12 D-coded Ethernet interface |
| Cellular Interfaces + Navigation | 1 LTE radio category 4, 3GPP E-UTRA release 11, MIMO DL with Rx diversity LTE, UMTS/HSPA+, GSM/GPRS/EDGE (worldwide) Single Nano SIM Multi-constellation GNSS (GPS, Galileo, GLONASS, Beidou). Requires an active antenna. |
| Cellular radio data rate | 150 Mbps ↓ & 50 Mbps ↑ (maximum radio data rate) |
| Cellular operating frequencies | LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B12/B13/B18/B19/B20/B25/B26/B28 LTE-TDD: B38/B39/B40/B41 WCDMA: B1/B2/B4/B5/B6/B8/B19 GSM: B2/B3/B5/B8 |
| WiFi Interface | 1 radio IEEE 802.11a/b/g/n 2T2R, 2.4 / 5 GHz, ANI (Adaptive Noise Immunity) |
| WiFi radio data rate | 802.11a: 6, 9, 12, 18, 24, 36, 48 and 54 Mbps 802.11b/g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48 and 54 Mbps 802.11n: MCS0-7, 2T2R 2 streams (6.5 to 300 Mbps) |
| WiFi operating frequencies | ISM : 2.4-2.483 GHz (up to 14 channels) UNII : 5.15-5.25 GHz (up to 4 channels) UNII-2 : 5.25-5.35 GHz (up to 4 channels) UNII-2 ext : 5.470-5.725 GHz (up to 11 channels) UNII-3 : 5.725-5.825 GHz (up to 4 channels) Supports DFS and TPC |
| Output power | WiFi : • 2.4 GHz : up to 20.5 dBm • 5 GHz : up to 18 dBm LTE / 4G : • GSM : up to 33 dBm |
| Sensitivity max | WiFi : • 2.4 GHz : -92 dBm • 5 GHz : -96 dBm LTE WCDMA B5/B8 : -110.5 dBm |
| Radio connectors | 5 fakra connectors : WiFi (2 x I-coded), LTE (2 x D-coded), GNSS (1 x C-coded) according to ITxPT standard |
| Security | Firewall, DoS, https, filtrage MAC, WPA2/WAP3-Personal & Enterprise (IEEE 802.1X radius), WEP, tunnels L2 (GRE), VPN (OpenVPN, IPsec), SNMP V3, isolation of clients in AP mode, Wireless Intrusion Detection System (WIDS) |
| WiFi Modes | AP, client, MESH (IEEE 802.11s), infrastructure, AD-HOC, fast roaming (less than 30 ms), WMM QoS |
| Ethernet networking | Frames filtering, bridging, repeater, STP/RSTP, VLAN, DHCP (server & client), DNS relay |
| Ethernet routing | Multicast (PIM), IP redundancy (VRRP), static routes, NAT router, router |
| Administration | http, https, SNMP agent (V1, V2C, V3), WaveManager administration software |
| LEDs signaling | Radio: activity and status Ethernet : link 10/100, activity Power : on-off Diagnostic |
| Power supply | 7 to 48 VDC, 3 point Phoenix connector or PoE 802.3af |
| Consumption | 9W typical power consumption / Recommended power supply: 12W |
| Dimensions & weight | Product: compact rugged aluminium enclosure, (147 x 41 x 100 mm), 420 g |
| Environment | IP40 seal rating • Operating: -20°C to +60°C (HR 0-99%) |
| Standards and certifications | CE (RED) Security : EN 62368-1, EN62311 CEM : EN301-489 Radio: • WiFi : EN 300 328 (2.4 GHz), EN 301 893 (5 GHz, DFS) • LTE : EN 301 908 [-1, -2, -13], EN 301 511, EN 303 413 |
| | FCC Radio: • WiFi : FCC ID Z9W-RMB • LTE : FCC ID 2ATM8EG25G, IC 25391-EG25G |
| | Automotive CEM : ECE R10 (UTAC E2/ R10) Environmental: • Shock and vibration : EN 61373 • Fire/smoke : UNR118, RoHS, WEEE |
| | Railway CEM : EN 50155 Environmental: • Shock and vibration : EN 61373 • Fire/smoke : EN45545 |
| Warranty | 5 years |

Ordering references

| | |
|-------------------------------|---|
| AirWan-M12/17 | WiFi router (802.11n)+ 4G/LTE (world) + multi-constellation GNSS interface, 2 ports Fast Ethernet, shipped without antennas |
| Additional accessories | |
| PWS12-UNI-PH3 | AC (110V / 220V) to 12VDC power adapter with cable terminated by a 3-pin Phoenix terminal block |

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.

ACKSYS_AirWan-M12_US_14/02/23