

# COMETH-FIELD-RD

RS232 / RS422 / RS485 DIN Rail single port server



- DIN Rail format
- RS232, RS422, RS485 interfaces
- Easy administration from serial port or Ethernet
- MODBUS/TCP (Client / Server) protocol support
- Raw, Mux., and COM ports re-direction modes
- Metallic case, CE standards



## Introduction

COMETH range products give access to any serial equipment from Windows, Unix & Linux computers connected to your Ethernet TCP/IP network, making it possible to communicate between two distant serial equipments through the network or even build an Ethernet / MODBUS gateway.

These products feature a very high integration and a very small form factor.

The support of the Telnet (RFC 2217) extension associated to a COM ports re-director enables distant serial equipments connected to the COMETH to be directly used by Windows & Linux existing applications using standard COM ports.

COMETH combines the flexibility and the power of the TCP/IP protocol as well as the universality of the Ethernet networks.

## Technical characteristics overview

<b>Serial port</b>	Single asynchronous serial port, up to 230.4 Kbps 7 or 8 bits per character, 1 or 2 stop bits, even, odd, mark, space or no parity Hardware hand-shake (RTS/CTS) and/or software hand-shake (XON/XOFF)
<b>RS signals available</b>	RS232 : TxD, RxD (3 Tx signals, 5 Rx signals), RTS, DTR, CTS, DCD, DSR, RI RS422/485 : -Tx, +Tx, -Rx, +Rx. +RX and -RX signals can be polarized (jumpers)
<b>Connectors</b>	Male SUB D9 (RS232) & female SUB D9 (RS422/485)
<b>Protection</b>	15KV ESD protection with HF signal filtering, CE conformity, RS/Ethernet 1500 Veff isolation
<b>Ethernet network</b>	Ethernet 10/100 «auto-sensing» & «auto MDI / MDIX cross-over»
<b>Modes</b>	Support for TCP Client/Server, DHCP Client, TELNET RFC2217 extension, Telnet Server, COM port re-director (VIP), multipoint or point to point virtual link over UDP modes and MODBUS/TCP Client/Server, MODBUS/RTU & MODBUS/ASCII protocols
<b>Administration</b>	From the serial port or through Ethernet (Telnet), firmware download for easy upgrade
<b>Operating systems</b>	Any compatible TCP/IP system
<b>Signaling</b>	1 power LED, 1 diag. LED, 1 serial LED & 2 LAN LEDs
<b>Power supply</b>	External power supply +9VDC to +36VDC
<b>Dimensions &amp; weight</b>	L73 x l76 x h29 mm, 120 g
<b>Environment</b>	Operating temperature: -40°C to +80°C

## Ordering references

COMETH-FIELD-RD	RS232/RS422/RS485 to Ethernet TCP/IP single port server, with COM ports re-director & MODBUS/TCP
-----------------	--

*All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.*