

RailBridger

Compact wireless inter-carriage link



- Point-to-point interconnection solution operating in license-free 60 GHz frequency bands
- Based on the 802.11ad standard
- 1.2 Gbps connectivity
- Very Compact size with integrated beamforming antenna
- Rugged device designed for railway: shocks & vibrations proof, wide temperature range -40°C to +70°C, EN50155 and EN 45545-2 certified
- Plug & play installation
- Powered by standard PoE switch (802.3af)
- Support of dynamic carriage composition



802.11ad



Introduction

The RailBridger ACKSYS is a product designed specifically for inter-car and inter-train wireless connection.

It is the ideal solution for train refurbishment or modernization projects, where there is no IP backbone or where the on-board network is limited (100 Mbps). Using wireless couplers is much easier and more cost-effective than using cables.

- High throughput: use of the 60GHz band avoids interference with 2.4GHz and 5 GHz WiFi, and enables very high data rates of the order of 1.2Gbps.
- Extremely compact dimensions
- Plug&Play: easy mechanical installation (4 screws), PoE power supply and virtually no configuration required
- Intelligent inter-car coupling: the wireless IP backbone automatically reconfigures itself to adapt to any changes in car composition.
- Redundancy: two RailBridger couplers can be used on either side for redundancy or link aggregation.
- Highly robust: IP-69K

Technical characteristics overview

Physical interfaces	Outdoor Unit with integrated antenna PoE interface: outdoor CAT-5e or CAT-6 via M12 X-coded connector; Maximum cable length: 75m for 2500BaseT Mounting by 4 screws with flanges or external mounting plate	
Radio data rate	Max Capacity: Up to 1.5Gbps Channel Bandwidth: 2.16GHz Modulation: BPSK, QPSK, QAM (MCS 1-8); Single Carrier	
Output power	Up to 32dBm EIRP	
Performance	Link Acquisition time 5 seconds	
Ethernet routing	Layer 2 Bridge Mode	
Security	Management VLAN, SNMP v3, Encryption AES 128	
Administration	SNMP v3; HTTPS using web browser	
Operating frequencies	EN 302 567 V2.1.1 - Operation within the band 57-66 GHz	
Dimensions and weight	12x12x2.25 cm / 300g and 440g with mounting plate	
Power supply	802.3af standard PoE	
Consumption	Up to 12W	
Environment	Operating Temperatures -40° to +70°C Storage Temperatures -40° to +85°C IP-69K, NEMA-type 4	
Standard and certifications	US/CAN (cTUVus)	UL 62368-1, UL 60950-22, CAN/CSA C22.2 62368-1, CAN/CSA C22.2 60950-22
	CE/IEC	EN/IEC 62368-1, EN/IEC 60950-22
	FCC	47 CFR Part15, Subpart B, Class B
	CE	EN 301 489-1, EN 301 489-17
	CAN/CSA-CEI/IEC	ICES-003: 2017 Issue 6, Class B
	AS/NZS	CISPR 32-2015 Class B
	EMC	EN 50121-3-2, EN 50121-4 Class B, EN 50155
	Electronic	EN 50155, IEC 60571
	Shock & Vibration	EN 61373, EN 50155, IEC 60571
Fire/smoke	EN 45545-2	
Warranty	Default 2 years, and can be extended to 5 years	
Reliability	MTBF >131,400 Hours for outdoor and rail environment	

Ordering references

RailBridger	Wireless inter-carriage link 802.11ad, with an integrated antenna, supporting 60 GHz ETSI frequency band
-------------	--

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.

ACKSYS_RailBridger_US_Rev A1_11/09/23